



INTERIOR VARNISH GLOSS

Crown Trade Interior Varnish is a high quality varnish in a clear finish and will protect and enhance all interior surfaces, providing a scuff and water resistant finish which is easy to clean.

AVAILABILITY

Colour range Clear only.

Packaging 750mls & 2.5 litre

PROPERTIES

Drying time Under normal drying conditions surface dry 4-6 hours and recoatable after 16 hours. Allow for adequate ventilation during the drying period.

Finish Gloss.

Composition
Pigment: None.
Binder: Alkyd and Urethane.
Solvent: Dearomatised White Spirit.

Spreading rate 15m² per litre on smooth surfaces

Wet film thickness 66 micrometres at 15m² per litre.

Dry film thickness 29 micrometres at 15m² per litre.

Volume solids 43%

Flash point 40°C (closed cup)

VOC content EU limit value for this product (cat.A/e): 500 g/l (2007) / 400 g/l (2010)
This product contains max. 499 g/l VOC.

Limitations For interior use only. Do not apply when air or substrate temperatures are likely to fall below 8°C or when the relative humidity is above 80% during application or the drying period.

PREPARATION

New surfaces All surfaces must be suitably dry, and free from anything that will interfere with the adhesion of the materials to be applied. Rub down with a suitable grade of abrasive paper and round sharp edges 1-3mm. Remove all dust. Timber with oils/extractives must be swabbed with clean dearomatised white spirit, frequently changing the face of the cloths. Fill any fixing holes, open joints and shallow surface defects with a suitable proprietary wood filler to match the colour of the bare timber. Rub down with a suitable grade of abrasive paper. Remove all dust.

Previously decorated surfaces

All surfaces must be suitably dry, and free from anything that will interfere with the adhesion of the materials to be applied. Remove all loose, and failing or suspect coatings. Feather edges of sound coatings. Remove all dust. Organic growth must be removed and the areas treated with Crown Trade Fungicidal Solution. Fill any fixing holes, open joints and shallow surface defects with a suitable proprietary wood filler to match the colour of the bare timber. Rub down with a suitable grade of abrasive paper. Remove all dust. Spot prime bare and filled areas with one coat of Crown Trade Interior Varnish. Wash all remaining sound coatings with hot water and liquid detergent solution to remove any contaminants, frequently changing the water. Rinse with clean water to remove all residues. Allow to dry. Bring forward all spot primed areas with one coat of Crown Trade Interior Varnish.

APPLICATION Stir well before use. Apply by brush to an even thickness (a fine, soft filament bristle brush gives the best results). Maintain a wet edge and lay off in the direction of the grain.

COATING SYSTEM Apply two or three coats as required. For best results denib between coats.

CLEANING Return surplus material to container. Clean with a proprietary cleaner immediately after use.

MAINTENANCE INFORMATION FOR CDM FILE

Between maintenance redecoration surfaces may be washed with a warm water and liquid detergent solution to remove surface dirt.

HEALTH AND SAFETY Please refer to the Safety, Health and Environmental Information on the container. Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead. For further information contact the Akzo Nobel Customer Advice Centre. When preparing all surfaces avoid the inhalation of dust and/or metal particles. Wear a suitable facemask. Material Safety Data Sheets for this and all other Akzo Nobel products are freely available from the place of purchase or the address below. Store in secure dry conditions inaccessible to children or animals. Containers should be kept closed during storage. Do not empty into drains, watercourses or access routes to septic tanks.

GENERAL INFORMATION

Apply all products in accordance with BS 6150: 2006 Code of practice for painting of buildings and BS 8000: Part 12: 1989 Code of practice for decorative wallcoverings and painting. Under normal and frost free conditions this product will remain usable for up to two years if stored correctly and unopened.

Every care is taken to ensure that all information provided on this Technical Data Sheet is accurate. Akzo Nobel Decorative Coatings Ltd. is unable to guarantee results as it has no control over the conditions under which its products are applied.

For help or more information contact the Akzo Nobel Customer Advice Centre 0870 241 6457. Before using this product please ensure you have the latest information. The information is correct at date of issue Aug 2006.

